

			22023010002903
Indoor Model			MTI-24HWFNX-QRD0
Indoor code			22023011003014/ MTI-24FNXD0
Outdoor Model			MOCA30U-24HFN8-QRD0
Outdoor code			22022516001182
Average	Pdesignc	kW	7.0
	SEER	W/W	6.1
	Energy Efficiency Class		A++
	Pdesignh	kW	5.1
	SCOP	W/W	4.0
	Energy Efficiency Class	℃	A+
	Tbiv		-7
	Tol		-15
Warmer	Pdesignh	kW	6.1
	SCOP	W/W	5.1
	Energy Efficiency Class	℃	A+++
	Tbiv		2
Power supply (Indoor)		V- Ph-Hz	220-240V,1Ph,50Hz
Power supply (Outdoor)		V- Ph-Hz	220-240V,1Ph,50Hz
Cooling	Capacity	Btu/h	24000(7500-28300)
	Capacity	kW	7.03(2.20-8.21)
	Input	W	2190(480-2850)
	Current	A	9.5(2.1-12.4)
Heating	Capacity	Btu/h	26000(8300-29500)
	Capacity	kW	7.62(2.43-8.65)
	Input	W	2050(500-2880)
	Current	A	8.9(2.2-12.5)
Indoor fan motor	Model		ZKFN-160-8-1-2
	Old Model		/
	Qty		1
	Input	W	90.0
	Capacitor	uF	---
	Speed(Hi/Med/Lo)	r/min	1200/-/-
Indoor air flow		m3/h	1248/1054/839
ESP	Rated	Pa	25
	Range	Pa	0-160
Indoor sound pressure level		dB(A)	44/42/40
Indoor sound power level		dB(A)	62
Indoor unit	Dimension (WxDxH)	mm	1100x774x249
	Packing(WxDxH)	mm	1305x805x305
	Net/Gross weight	kg	31.5/38.9
Design pressure		MPa	4.6/1.7
Drainage water pipe diameter		mm	ODΦ25mm
Refrigerant piping	Liquid side/ Gas side	mm	Φ9.52/Φ15.9(3/8"/5/8")
Controller		Standard	Wired control
Operation temperature		℃	17-30
Room temperature	Cooling	℃	17~32
	Heating	℃	-15~50
Qty/per 20' /40' /40'HQ		Indoor unit	77/161/184

Remarks: 1. The above design and specifications are subject to change without prior notice for product improvement